

(Qubes)

PRODUCT SHEET

OSCARONO
PARIS



SHAKE
THE
LINES



QUBES COLLECTION

BASIC ENDGRAIN FOUNDATION FOR GREAT PROJECTS

Qubes has been engineered because sometimes a project is on a budget-leash while the floor needs to offer all technical and aesthetical advantages of endgrain.

Qubes is made of European oak end-grain that offers hardness, durability and improved acoustics.

We invite you to discover Qubes, an engineered endgrain flooring at democratic prices.



DIMENSIONS

Width of the board:	80 mm
Thickness of the board:	16 mm
Thickness toplayer	6 mm
Size oak blocks	80x80 mm
Length of the board	1138 mm
Sqm per board	0,091 m ²
Weight per sqm	12 kg

FINISH

Unfinished - Natural - Black - Smoke

TIMBER SPECIE

European Oak / Quercus Robur

CERTIFICATION COMPLIANCE

FSC/PEFC	On request
CE	EN 14342
VOC emissions	E1/ISO 16000
Fire resistance rating	Cfl-S1
Brinell hardness rating	3.7 (medium-hard wood: 2.5 to 3.8)
Thermal resistance	0.14 m ² K/W (depending on the installation surface)

USE

In- / outdoor	Indoor only
Area	Avoid high humidity areas, like spa
Traffic	High traffic area, residential and commercial (classification 33)

HS CODE

4409 2991 00

SPECS MIX GRADING

Grow defects:	10 mm
Knots:	max. 40 mm/ in max. 1 pieces of board, filled
Sap wood:	max. 20 mm, stained
Water spots:	yes
Worm holes:	no
Dark color shades (brown core):	no
Drying stripes:	no
Cracks:	<10mm, filled
Rouge:	no

CONSTRUCTION

Plywood	10 mm - 100% Birch waterproof quality, D4 adhesives
Oak toplayer	6 mm
Adhesive toplayer	1 component glue with ISO normation 17178.
Connection boards	(Loose) Tongue and groove system
Bevel	N/A
Oak Blocks	Round Gap approx 1 mm

CLIMATIC CONDITIONS

Wood products	8-12% moisture
Ideal indoor environment	40-60% humidity

PACKAGING

Max. palletsize	120x80x100 cm
Max. boards on a pallet	520 pcs
Max. m ² on a pallet	40
Max. pallet weight	500 kg



made@oscarono.fr
oscarono.fr

